

TITEBOND® INSTANT BOND WOOD ADHESIVE - THICK

PHYSICAL PROPERTIES

Type: Ethyl cyanoacrylate
State: Liquid
Color: Clear
Dried film: Translucent
Solids: 100%
Viscosity: 2,400 cps
Specific gravity: 1.1

Calculated VOC (less water): 20 g/L
Weight/gallon: 9.18 lbs.
Flashpoint: >178° F.
Freeze/thaw stability: Stable
Storage life: 2 years in tightly closed containers stored between 40° and 75° F.

APPLICATION GUIDELINES

Application temperature Above 50°F.
Cure speed 10 second handling, 8 second set, 30 second cure. *Full cure in 8 hours.
Service temperature range -65° to 200° F.
Cleanup Use acetone. Follow solvent vendor's precautions.

BOND STRENGTH ASTM D-1002

Temperature	Shear Strength psi
Room Temperature	Between 2800 and 4200 psi depending on substrate tested

PRODUCT FEATURES

- Fast set—eliminates clamping or reduces clamp time
- Bonds stronger than wood
- Excellent heat and solvent-resistance
- Unaffected by finishes
- Versatile—bonds wood, MDF, acrylic, granite, natural rubber, PVC and more
- 2 year shelf life
- Triple distilled for purity & consistency
- Impact-resistant
- No-clog applicator for easy use and waste reduction
- Ideal for bonding miter joints on MDF and porous woods
- Designed for finish & trim carpentry
- High viscosity allows time for positioning parts
- MIL Spec (A46050C) Type II, Class 3

LIMITATIONS

Titebond Instant Bond Wood Adhesive is not intended for exterior use or where moisture is likely. Store in a cool, dry place. Handling and set times may be affected by environmental conditions. For best results, apply adhesive between 55°F and 85°F. **KEEP FROM FREEZING.**

CAUTIONS

DANGER: COMBUSTIBLE LIQUID. Bonds skin, eye and other tissue instantly. Contains ethyl-2-cyanoacrylate. Irritating to eyes, skin and respiratory tract. Do not allow eye or skin contact. Avoid breathing vapors. Do not swallow. Keep away from sources of heat. **FIRST AID:** For eye contact, do not force eyes open. Flush eyes with water for 15 minutes and seek medical attention immediately. For skin contact, flush contact area with water and seek medical attention. If inhaled, remove to fresh air. Seek medical assistance if symptoms persist. Refer to Material Safety Data Sheet for additional information. **KEEP OUT OF THE REACH OF CHILDREN.**

ORDERING INFORMATION

Cat. No.	Size	Units per Package	Weight	Packages per Pallet
6221	2 oz. Bottle	15	3	210
6222	4 oz. Bottle	10	3	270
6223	8 oz. Bottle	10	6	144

Important Notice: Our recommendations, if any, for the use of this product are based on tests believed to be reliable. Since the use of this product is beyond the control of the manufacturer, no guarantee or warranty, expressed or implied, is made as to such use or effects incidental to such use, handling or possession or the results to be obtained, whether in accordance with the directions or claimed so to be. The manufacturer expressly disclaims responsibility therefore. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and/or patents covering any material or use.

2020 Bruck Street, Columbus, Ohio 43207
 CUSTOMER SERVICE 1-800-669-4583
 TECH SERVICE 1-800-347-GLUE
 www.titebond.com

Franklin International
 ©2008 Franklin International. All rights reserved.