

# TITEBOND® WOOD FILLER

## PHYSICAL PROPERTIES (TYPICAL)

**Type** Water-based polymer  
**State** Paste  
**Color** Light Yellow  
**Solids** 76.5%  
**Viscosity** Paste  
**pH** 9.0

**Calculated VOC** (less water): 9.6 g/L  
**Weight/gallon** 16 lbs.  
**Flashpoint** >200°F.  
**Freeze/thaw stability** Stable  
**Storage life** 12 months in tightly closed containers at 75°F.

## APPLICATION GUIDELINES

**Application temperature** 40°F. to 100°F. for wood filler and substrates  
**Service temperatures** -20°F to 200°F.  
**Method of application** Spatula, putty knife  
**Container sizes** 4, 8 and 16 oz. plastic containers  
**Working surfaces** Should be free of excessive dirt and dust. Do not apply to finished surfaces.  
**Working time** Approximately 10 minutes, depending upon temperature and humidity.  
**Cleanup** Water when wood filler is still wet. Sand off excess wood filler if dried.

## PRODUCT FEATURES

- Latex formula is stronger than solvent-based products
- Excellent sandability when dry
- Can also be cut, sawed, planed or drilled
- Nonflammable
- Hardens like wood
- Accepts stains easily
- Cleans up with water

## ORDERING INFORMATION

Cat. No.	Size	Units per Package	Weight	Packages per Pallet
5362	4 oz. Plastic Container	12	6	228
5363	8 oz. Plastic Container	12	13	156
5364	16 oz. Plastic Container	12	25	76

## CAUTION STATEMENT

**CAUTION: EYE AND SKIN IRRITANT.** Do not swallow. Do not allow eye contact or prolonged skin contact.  
**First Aid:** If swallowed do not induce vomiting, contact physician. If eye contact occurs, flush eyes with water for 15 minutes. Wash skin contact areas with soap and water. If irritation from eye or skin contact areas persists, contact physician. For additional information, refer to Material Safety Data Sheet.  
**KEEP OUT OF THE REACH OF CHILDREN.**

**Important Notice:** Our recommendations, if any, for the use of this product are based on tests believed to be reliable. Since the use of this product is beyond the control of the manufacturer, no guarantee or warranty, expressed or implied, is made as to such use or effects incidental to such use, handling or possession or the results to be obtained, whether in accordance with the directions or claimed so to be. The manufacturer expressly disclaims responsibility therefore. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and/or patents covering any material or use.

2020 Bruck Street, Columbus, Ohio 43207  
CUSTOMER SERVICE 1-800-669-4583  
TECH SERVICE 1-800-347-GLUE  
www.titebond.com

# Franklin International

FF522 (Rev. 4/01) © Copyright 2001 Franklin International. All rights reserved.